

EARTHWOOL RAINSCREEN SLAB

December 2018



APPLICATIONS



DESCRIPTION

Earthwool RainScreen Slab is a semi-rigid, lightweight, non combustible Rock Mineral Wool slab containing a water repellent additive, specifically designed for use in rainscreen cladding systems both below and above 18m in height.

PERFORMANCE

Thermal

Thermal conductivity: 0.034 W/mK

Fire

Classification: Euroclass A1 to BS EN 13501-1

Vapour resistivity

Water vapour resistivity: 5.00MN_s/g.m

Wind Load

Wind fatigue testing 3.6kPa

BENEFITS


- ✓ Non-combustible Euroclass A1 Reaction to Fire rating
- ✓ Excellent water resistance
- ✓ Rigid and robust
- ✓ Designed to adapt to minor imperfections in substrates

SPECIFICATIONS

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m ² K/W)	Length (mm)	Width (mm)	Pieces per pack	Area per pack (m ²)	Packs per pallet
210	0.034	6.15	1200	600	N/A	17.28	N/A
200	0.034	5.85	1200	600	N/A	17.28	N/A
180	0.034	5.25	1200	600	3	2.16	10
150	0.034	4.40	1200	600	3	2.16	12
120	0.034	3.50	1200	600	4	2.88	10
100	0.034	2.90	1200	600	4	2.88	12
75	0.034	2.20	1200	600	6	4.32	12
50	0.034	1.45	1200	600	8	5.76	12

All dimensions are nominal

CERTIFICATION



EARTHWOOL RAINSCREEN SLAB

December 2018

ADDITIONAL INFORMATION

Durability

Earthwool RainScreen Slab is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria. The product will have a life equivalent to that of the wall structure in which it is incorporated

Application

Earthwool RainScreen Slab is used for the thermal insulation of rainscreen cladding systems. Earthwool RainScreen Slab is lightweight but rigid enough to resist the compression forces generated when fixing the insulation slabs to the buildings substrate. The water repellent additive in Earthwool RainScreen Slab provides a further line of defence against rain penetration.

Standards

Earthwool RainScreen Slab is manufactured in accordance with BS EN 13162, ISO 50001 Energy Management Systems, OHSAS 18001 Occupational Health and Safety Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management Systems, as certified by Bureau Veritas.

Environmental

Earthwool RainScreen Slab represents no known threat to the environment and has zero Ozone Depletion Potential and zero Global Warming Potential. Earthwool RainScreen Slab has a generic BRE Green Guide rating of A+. Earthwool RainScreen Slab is covered by Environmental Product Declaration BREG EN EPD No. 000096, ECO EPD Ref. No.: 000325 in accordance with the requirements of EN 15804.

Vapour resistivity

Earthwool RainScreen Slab offers negligible resistance to the passage of water vapour and has a water vapour resistivity of 5.00MN/g.m.

Moisture

The physical and chemical characteristics of the fibres are unaltered by wetting. Therefore we can state that the thermal properties of Earthwool RainScreen insulation slab are not affected by exposure to moisture and the product will perform as expected once dry.

Thermal performance

The U-value of a proprietary rainscreen cladding system is dependent on the degree of thermal bridging in the system. Calculations should be created using 2D or 3D modelling programs which comply with the methodologies detailed in BS EN ISO 10211.

Knauf Insulation offer 3D numerically modelled U-value calculations compliant with BS EN ISO 10211 under the BBA/TIMSA U-value and Condensation Risk Analysis Competence Scheme.

Handling and storage

Earthwool RainScreen Slab is easy to handle and install, being lightweight and easily cut to size, where necessary. Earthwool RainScreen Slab is supplied in polythene packs which are designed for short term protection only. For longer term protection on site, the product should either be stored indoors, or under cover and off the ground. Earthwool RainScreen Slab should not be left permanently exposed to the elements.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

Knauf Insulation Ltd

PO Box 10, Stafford Road, St.Helens, Merseyside, WA10 3NS. UK

Customer Service: 0844 800 0135

Technical Support Team: 01744 766 666

Literature: 08700 668 660

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINE1517DAF-V1218

challenge.
create.
care.