



VALPAINT s.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
E-mail: info@valpaint.it
C.F./P.IVA/R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it

SC 00222

## **ADDITIVO SILVER G 200**

## **Technical Sheet:**

NAME: ADDITIVO SILVER G 200
TYPE: Water-based silver additive

<u>USE:</u> To be added to Klondike or Klondike Light to get silvery shadows

**CHARACTERISTICS:** specific weight: 1.070± 30 gr/LT. at 25°C

viscosity: = = =

yield: LT. 0,100 per LT. 1 of Klondike or Klondike Light LT. 0,250 per LT.2,5 of Klondike or Klondike Light

aesthetic effect: silvery reflections

colours: silver like

packaging: LT. 0,100 - LT. 0,250

**DRYING:** on surface: ===

over painting: = = = = in depth: = = = =

CHARACTERISTICS AND

PREPARATION OF THE

**RESISTANCE:** 

product stable to light and resistant to washing . Add to Klondike or

Klondike Light to give silvery reflections to the paint.

PREPARATION OF THE =

**SUPPORT:** 

**PRODUCT:** 

**dilution:** ready to use. Add to Klondike or Klondike

Light and mix well

catalization relation: = = =

**pot life:** = = =

**APPLICATION:** system: add the Additive Silver G 200 in Klondike

or Klondike Light already coloured can

and mix well

number of coating: = = =

## **NOTES:**

- Working tools must be washed carefully soon after use with water
- Storage and application temperature must be superior to +5°C and inferior +30°C.

Technical Sheet  $n^{\circ}$  SC 00222 issued by the Control Responsible of Quality

Edition n° 2 December 2011